



CODEMARK™

CERTIFICATE OF CONFORMITY

This is to certify that

Termiglass Non-Toxic Physical Termite Management System



Product description
<p>The Termiglass Non-Toxic Physical Termite Management System comprises :</p> <ul style="list-style-type: none"> • Termiglass is graded glass screenings used as a termite barrier. The glass material ranges in size from 1.2mm to 3mm. The Termiglass is installed into the base of the perimeter wall cavity in conjunction with termite strip shielding. The compacted dimension of Termiglass shall be not less than 75mm in depth and 25mm in width. • Termicide Frizbee is manufactured in 40, 50, 80 and 100 mm diameter sizes, is manufactured from rigid plastic collars, made with an internal diameter slightly under the outside diameter of the pipe to ensure a tight fit. • Termicide Sealant is a silicone based sealant that is termite resistant, used at joints in termite resistant materials
Product purpose or use
<p>Termiglass is a physical termite management measure to deter concealed subterranean termite entry into a building or structure.</p>
Certificate holder
<p>Termicide Pty Ltd 7 Technology Drive, Arundel QLD 4214</p>

<p>Complies with the Building Code of Australia 2009:</p> <ol style="list-style-type: none"> 1) Volume One: BP1.1 (limited only to actions by subterranean termites in clause BP1.1(b) (xv) and B1.4 (i)) 2) Volume Two: P2.1 (limited only to actions by subterranean termites in clause P2.1(b) (xv) and 3.1.3) 3) State Variation: Volume Two – QLD P2.1.1 (a), (b) (limited only to actions by subterranean termites) <p>Subject to the following conditions and limitations:</p> <ol style="list-style-type: none"> 1) Does not comply with the Building Code of Australia Volume 1 Northern Territory Variation <i>NT B1.4(i)</i> 2) The Termiglass System has not been appraised for use North of the Tropic of Capricorn. 3) Installed by Termicide Pest Control accredited installers (holder of a current Installer Card) 4) Product installation, shall be carried out in accordance with the Termicide Installation Manual version 1.0 dated 01/04/2009 5) The durable notice installed in accordance with BCA Volume One: B1.4 (i)(ii) and BCA Volume Two: 3.1.3.2(b) must be permanently fixed to the building in a prominent location, such as a meter box or the like indicating: <ol style="list-style-type: none"> a) The method of termite risk management; and b) The date of installation of the system; and c) The manufacturer's recommendations for the scope and frequency of future inspections for termite activity. 6) When used as a termite management measure in conjunction with a concrete slab the slab must be designed and constructed according to AS 2870: 1996 (up to amendment 4, 05/2003) or AS 3600: 2001 (up to amendment 2, 10/2004). 7) When used as a termite management measure in masonry walls, the mortar joint below shall be full (have no gaps or porosity to assist in provision of a visual inspection zone) 8) Where exposed in a construction joint, the Termiglass shall be capped or sealed with Termiglass capping compound. The Termiglass must extend for the full length of the joint and interface with the perimeter management measure at the ends for continuity. 9) Termiglass is used internally at the base of perimeter wall cavities and where the adjoining external masonry wall is not termite resistant; termite strip shielding is incorporated into that masonry and is folded vertically such that it penetrates into the Termiglass to a depth of not less than 35mm. 10) All penetrations are collared with not less than 25mm width x 75mm depth of compacted Termiglass, penetrations passing through perimeter Termiglass encased in not less than 25mm of Termiglass and capped with Termiglass capping compound or fitted with Termicide Frizbee 11) Inspections are undertaken annually in accordance with the Termicide Installation Manual to determine that no bridging or breaching of the Termite Management System has occurred.



CodeMark Certification Body			22/07/2009	21/09/2009	22/07/2012	GM-09-CM30014
Global-Mark Pty Ltd, Suite 4.07, 32 Delhi Road, North Ryde NSW 2113, Australia - www.Global-Mark.com.au	Herve Michoux Managing Director	Unrestricted Building Certifier, Peter Gardner	Date of issue	Last update	Date of expiry	Certificate Number

- This Certificate of Conformity is issued under arrangement with JAS-ANZ. The ABCB does not in any way warrant or represent that the Product the subject of this Certificate of Conformity conforms with the BCA, nor accepts any liability arising out of the use of the Product.
- It is advised to check that this Certificate of Conformity is currently valid and not withdrawn, suspended or superseded by a later issue by referring to the ABCB website, www.abcb.gov.au.